

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) An electrode for a fuel cell comprising:
a gas diffusion layer; and
a catalyst layer formed over said gas diffusion layer;
wherein said catalyst layer comprises a first carbon particle having a hydrophilic surface,
a catalytic metal supported on said first carbon particle, an ion exchange resin and a second
carbon particle having a water-repellent surface;
a content of said second carbon particle in the catalyst layer is in a range of 10wt.% to
50wt.% with respect to a weight of the entire catalyst layer; and
a content of the first carbon particle, the catalytic metal and the ion exchange resin in the
catalyst layer is at least 50wt.% with respect to a weight of the entire catalyst layer, wherein
the electrode does not include any additional water-repellent materials other than the
second carbon particles, [[and]]
said gas diffusion layer includes the first carbon particle and the second carbon particle
and
a content of the second carbon particle in said gas diffusion layer is in the range of 3wt.%
to 30wt.% with respect to a weight of the entire gas diffusion layer.

2. (Original) The electrode for a fuel cell as set forth in Claim 1, wherein an average
value of lattice spacing of the [002] plane, d_{002} , of said second carbon particle is not less than
0.337nm but not greater than 0.348nm.

3. (Original) The electrode for a fuel cell as set forth in Claim 1, wherein a crystallite size in a direction of c-axis, $L_c(002)$, of said second carbon particle is not less than 3nm but not greater than 18nm.

4. (Original) The electrode for a fuel cell as set forth in Claim 2, wherein a crystallite size in a direction of c-axis, $L_c(002)$, of said second carbon particle is not less than 3nm but not greater than 18nm.

Claims 5-8 (Cancelled)

9. (Original) A fuel cell comprising:
an electrode for a fuel cell on fuel supply side;
an electrode for a fuel cell on oxygen supply side; and
a solid polymer electrolyte membrane placed between said electrodes;
wherein at least said electrode for a fuel cell on oxygen supply side is said electrode for a fuel cell as set forth in Claim 1.

10. (Original) A fuel cell comprising:
an electrode for a fuel cell on fuel supply side;
an electrode for a fuel cell on oxygen supply side; and
a solid polymer electrolyte membrane placed between said electrodes;
wherein at least said electrode for a fuel cell on oxygen supply side is said electrode for a fuel cell as set forth in Claim 2.

11. (Original) A fuel cell comprising:
an electrode for a fuel cell on fuel supply side;
an electrode for a fuel cell on oxygen supply side; and
a solid polymer electrolyte membrane placed between said electrodes;
wherein at least said electrode for a fuel cell on oxygen supply side is said electrode for a
fuel cell as set forth in Claim 3.

12. (Original) A fuel cell comprising:
an electrode for a fuel cell on fuel supply side;
an electrode for a fuel cell on oxygen supply side; and
a solid polymer electrolyte membrane placed between said electrodes;
wherein at least said electrode for a fuel cell on oxygen supply side is said electrode for a
fuel cell as set forth in Claim 4.

Claims 13-16 (Cancelled)

17. (New) The electrode for a fuel cell as set forth in Claim 1, wherein a content of
the first carbon particle in said gas diffusion layer is in the range of 1wt.% to 20wt.% with
respect to a weight of the entire gas diffusion layer.